

# Stratos ESD

(STR-1-ESD)



|                        |                                                                                                                      |
|------------------------|----------------------------------------------------------------------------------------------------------------------|
| Chair height:          | 605—855 mm                                                                                                           |
| Height range:          | 250 mm                                                                                                               |
| Seat depth:            | 460mm                                                                                                                |
| Seat width:            | 460 mm                                                                                                               |
| Tilt angle adjustment: | 21° backrest<br>11° seat                                                                                             |
| Back height:           | 460mm                                                                                                                |
| Back width:            | 440mm                                                                                                                |
| Glides:                | ESD black polyamide glide                                                                                            |
| Conductivity:          | $R = 10^4 \text{ Ohm}$                                                                                               |
| Standards:             | EN 12527, EN 12528, EN 12529<br>DIN EN ISO 14001 : 2005                                                              |
| Load capacity:         | 50 kgs                                                                                                               |
| Fabric:                | Camira Hi Tech                                                                                                       |
|                        | Electrical resistivity:<br>ISO 61340-5-1<br>Resistance to groundable point<br>Shall not exceed $10^{10} \text{ OHM}$ |
|                        | Flammability:<br>EN 1021-1<br>EN 1021-2<br>BS 7176 Low Hazzard                                                       |